

EN LHFSW / LHFMG / LHFRG product information sheet

Colours



LHFSW / LHFMG / LHFRG

Horizon pendant light fixed – black | moss green | rose gold

General product information:

Product:	Linear pendant light for direct and indirect lighting
Product highlights:	Available in three different colours, can be gesture controlled, infinitely dimmable, with five colour temperature settings, height-adjustable lighting fixture (via stop beads in the ceiling housing)
Safety and warning information:	See operating and installation instructions
Energy efficiency class:	

PISLHFEN-10001

LHFSW / LHFMG / LHFRG

Horizon pendant light fixed – black | moss green | rose gold

Technical data

Supply voltage / frequency	220–240 V / 50–60 Hz
Maximum power consumption	40 W
Connection clamp	3-pin
Power consumption in standby mode	< 0.5 W
Ceiling housing dimensions (W × D × H)	670 × 53 × 41 mm
Light dimensions (W × D × H)	1259 × 35 × 14 mm
Weight (incl. accessories / packaging)	4.9 kg
Surface material	Metal/plastic
Lighting control system / dimmable	Gesture control / yes
Light bulb / light colour	LED / warm white to cold white
Colour temperature / colour rendering index (Ra)	2700–5000 K / CRI > 90
Direct / indirect luminous flux	1600 lm / 770 lm
Direct beam angle	63° / 69°
Life cycle / switching cycles	> 50,000 hrs / min. 50,000
Protection class / protection type	1 / IP20
Energy efficiency class	G

Product description

Compact 2-in-1 lighting, simple operation using gesture control, height can be adjusted without tools

Scope of delivery

Horizon pendant light fixed, operating and installation instructions, installation template

Product and planning information

Installation aids must be provided at the installation site, remote control is not possible, can be installed on sloping ceilings with a gradient up to 3°

