

EN LSLSW / LSLMG / LSLRG product information sheet

Colours



LSLSW / LSLMG / LSLRG

Stars pendant light 3-light linear – black | moss green | rose gold

General product information:

Product:	Pendant light with 3 linear lighting fixtures
Product highlights:	Available in three different colours, DALI-controlled, height-adjustable without tools
Safety and warning information:	See operating and installation instructions
Energy efficiency class:	

PISLSLEN-10001

LSLSW / LSLMG / LSLRG

Stars pendant light 3-light linear – black | moss green | rose gold

Technical data

Supply voltage	220-240 V
Frequency	50-60 Hz
Maximum power consumption	10.5 W
Connection clamp	5-pin
Power consumption in standby mode	< 0.5 W
Ceiling housing dimensions (W × D × H)	930 × 42 × 53 mm
Light dimensions (D × H)	14 × 330 mm
Weight (incl. accessories/packageing)	4.2 kg
Surface material	Metal/plastic
Lighting control system	Button / DALI
Dimmable	Yes
Light bulb / light colour	LED / warm white
Colour temperature / colour rendering index (Ra)	2700 K / CRI > 90
Luminous flux	690 lm
Direct beam angle	46°
Service life	> 50,000 hrs
Switching cycles	Min. 50,000
Protection class / protection type	1 / IP20
Energy efficiency class	G

Product description

- Individually height-adjustable without tools
- DALI-controlled

Scope of delivery

Stars pendant light 3-light linear, operating and installation instructions, installation template

Product and planning information

- Installation aids must be provided at the installation site

