

EN MS290 product information sheet



MS290

Multi-drawer 290 mm

General product information:

| | |
|---------------------------------|--|
| Product: | Heat drawer with variable functions; chamber volume: 50 L |
| Product highlights: | Warm crockery, regenerate food, thaw or keep warm, cook at low temperatures, push-to-open mechanism, second shelf level can be added, expanded range of functions in combination with the BORA X BO steam oven |
| Recess dimensions: | Height: 290-292 mm; width: 560-568 mm; depth: min. 560 mm |
| Safety and warning information: | See operating and installation instructions |

PISMS290EN-1000 1

MS290

Multi-drawer 290 mm

Technical data

| | |
|--|--------------------|
| Supply voltage | 220-240 V |
| Frequency | 50/60 Hz |
| Maximum power consumption | 810 W |
| Fuse protection | 1 × 16 A |
| Mains supply cable length | 1.8 m |
| Mains supply cable plug type | C13/E+F |
| Dimensions (width × height × depth) | 559 × 290 × 537 mm |
| Oven chamber dimensions (width × height × depth) | 525 × 247 × 410 mm |
| Cooking chamber volume | 50 L |
| Weight (incl. accessories/packaging) | 24 kg |
| Weight (net) | 20.7 kg |
| Maximum load | 25 kg |
| Temperature control range | 30-100 °C |
| Temperature levels | 1-6 |
| Time levels | 1-6 |

Product description

- Powerful and versatile
- High-quality materials (e.g. glass and metal)
- Push2Open – easy opening by lightly pressing the front of the drawer
- Intuitive operation (icon and audio-supported touch display)
- Minimalist design to match the BORA X BO (flush-mounted, handleless, All Black)
- Simple cleaning (shelf rack is dishwasher-safe)
- Pre-set programmes or manual temperature and time adjustment
- BORA Connectivity – expanded operating options and range of functions thanks to networking with BORA X BO

Functions

- Warm crockery
- Reheat food
- Keep food warm
- Defrost food
- Low-temperature cooking
- Delayed start

Scope of delivery

Multi-drawer 290 mm MS290, shelf rack, mains supply cable with plug type E + F, communication cable, 5 pairs of decorative trims (different widths), installation accessories, operating and installation instructions

Accessories

Multi-drawer shelf rack MSER, multi-drawer glass front 290 mm MSF290, multi-drawer mains supply cable type G MSNLG (UK, IE) / type J MSNLJ (CH) / type I MSNLI (AU)

Product and planning information

- Built-in appliances weighing up to 105 kg can be placed directly on top of the multi-drawer.
- The base panel must be fixed and designed to withstand the appliances' weight.
- The back panel of the kitchen unit must not be fitted behind the appliance.
- Up to 2 shelf racks can be used at the same time.

