

EN ULB3X product information sheet



ULB3X

Air purification box 3

General product information:

Product:	Odour filter with activated charcoal for the recirculation models of the BORA modular systems Professional 3.0, Professional 2.0 and Classic 2.0
Product highlights:	Service life approx. 600 hours or 3 years

PISULB3XEN-10001

ULB3X

Air purification box 3

Technical data

Dimensions (width × depth × height)	452 × 150 × 508 mm
Weight (incl. accessories/packaging)	approx. 6.5 kg
Housing material	Galvanised steel
Duct connection	BORA Ecotube
Filter material	Activated charcoal granules
Activated charcoal mass incl. carrier material	approx. 3 kg
Maximum filter service life	600 h (3 years)

Product description

- Suitable for Professional 3.0, Professional 2.0 and Classic 2.0
- Service life approx. 600 h/3 years
- Effective odour elimination
- Diverse installation options
- Complete BORA system

Scope of delivery

3 × activated charcoal cartridges, housing plinth, fixing screw set, 2 × mounting brackets, installation instructions

Product and planning information

- Activated charcoal filter set ULB3AS for replacement
- Shallow duct connection 245 × 89 mm
- Ensure a revision option
- A shallow duct connector EFV is needed to form a direct link between the air purification box and the shallow duct
- Clearance of at least 2 cm is required to replace the filter cartridges
- Ensure a minimum return flow aperture of 500 cm² (e.g. shortened plinth board or slatted plinth)
- Compatible with UUE3 and ULB3

