







Technical data

Supply voltage	220 – 240 V
Frequency	50/60 Hz
Maximum power consumption	3.68 kW
Maximum power rating	3.68 kW
Minimum fuse protection	1 x 16 A
Power supply cable length	1,5 m
Dimensions (width x depth x height)	327 x 515 x 75 mm
Weight (incl. accessories/packaging)	7.4 kg
Surface material	SCHOTT CERAN®
Cooktop power levels	1 – 9, (switching of 2-ring/roaster)
Number of cooking zone circuits front	1
Number of cooking zone circuits rear	2
Size of front cooking zone	Ø 180 mm
Size of rear cooking zone	Ø 120/180 mm
Size of cooking zone	Ø 180 x 410 mm
Front cooking zone output	1600 W
Rear cooking zone output	600 W/1600 W
Bridged cooking zone power	3680 W

Product description

- Free choice of cooktop
- Oversized roaster
- Roaster switching
- 2-ring switching
- Childproofing feature
- Cooking zone timers
- Timer
- Pause function
- Demo mode
- automatic heat up function

Scope of delivery

- HiLight cooktop CKCB
- mounting straps
- height adjustment plate set
- power supply cable (1,5m)

Product- and planning instructions

- Ensure sufficient ventilation of the area below the cooktop.