



Technical data

| | |
|---|--|
| Multiphase supply voltage | 380 - 415 V 2N/3N |
| Single-phase supply voltage | 220 - 240 V |
| Frequency | 50 - 60 Hz |
| Maximum power consumption | 7250 W (4200 W / 3600 W) |
| Three-phase power supply/fuse protection | 3 x 16 A (standard connection) |
| Two-phase power supply/fuse protection | 2 x 16 A |
| Single-phase power supply/fuse protection | 1 x 32 A (1 x 20 A / 1 x 16 A) |
| Dimensions (width x depth x height) | 580 x 515 x 199 mm |
| Weight (incl. accessories/packaging) | 20,2 kg |
| Surface material | Glass ceramic |
| Cooktop extractor power levels | 1 - 9, P |
| Cooktop power levels | 1 - 9, P |
| Front left cooking zone output | 400 W |
| Front right cooking zone output | 2300 W |
| Rear left cooking zone output | 900 W |
| Rear right cooking zone output | 1400 W |
| Front left cooking zone power setting output | 600 W |
| Front right cooking zone power setting output | 3000 W |
| Rear left cooking zone power setting output | 1350 W |
| Rear right cooking zone power setting output | 2100 W |
| Front left cooking zone size | Ø 95 mm |
| Front right cooking zone size | Ø 210 mm |
| Rear left cooking zone size | Ø 140 mm |
| Rear right cooking zone size | Ø 175 mm |
| Size of exhaust opening | 445 x 137 mm |
| Filter medium | Activated charcoal filter with ion exchanger |
| Filter material | Filter panel with fine filter |
| Maximum filter service life | 150 h (1 year) |

Product description

- Intuitive sControl control red
- eSwap - easy filter change
- effective odour removal
- Minimum volume
- Simple cleaning
- Optimum cooktop use
- Maximum storage space
- Automatic extractor control
- Ultra-compact design
- Minimalistic design

Scope of delivery

- Induction cooktop with integrated cooktop extractor - Recirculation
- Air inlet nozzle black
- stainless steel grease filter
- activated charcoal filter
- operating and installation instructions
- Template for cut-out on rear wall
- sealing tape
- height adjustment plate set
- Housing cover power supply
- Installation accessories for the power supply

Accessories

- Air inlet nozzle black PUEd
- Colourful inlet nozzles
- Stainless steel grease filter PUEF
- Activated charcoal filter PUAkF
- UDB25 sealing tape
- BKR580 cooktop frame
- Side frame USL5 15 / USL515AB

Product- and planning instructions

- The power supply cable must be provided at the installation site
- Front power socket
- The air purification box is fitted with a telescopic pull-out (extension to 80 mm) for connection to the back wall of the unit
- Ensure sufficient ventilation of the area below the cooktop.
- Installation type: flush or surface-mounted
- The drawers and/or shelves in the floor unit must be removable for maintenance and cleaning purposes
- Please note that induction-compatible cookware must be used on induction cooktops
- The cooktop extractor system can be combined with all BORA sockets