





## technical data

Supply voltage	220 - 240 V
Frequency	50/60 Hz
Maximum power consumption	3.7 kW
Maximum power rating	3.7 kW
Minimum fuse protection	1 x 16 A
Power levels	1 – 9, P
Weight (incl. accessories/packaging)	8 kg
Surface material	SCHOTT CERAN®
Back cooking zone dimensions	Ø 220 mm
Power supply cable	1.5 m (L, N, PE)
Dimensions (WxDxH)	340 x 515 x 73 mm
Front cooking zone dimensions	Ø 155 mm
Front cooking zone power	1200 W
Back cooking zone power	2000 W
Front cooking zone power setting	1400 W
Back cooking zone power setting	2300 W



## **Product description**

- Minimalistic design
- Compact size
- Modular system
- warming function • childproofing feature
- Cooking zone timers
- Pause function
- automatic heat up function
- pan size recognition
- residual heat display

## Scope of delivery

- Cl11 induction glass ceramic cooktop
- mounting straps
- sealing tapeglass ceramic scraper
- · height adjustment plate set
- operating and installation instructions

- product- and planning instructionsPlease note that induction-compatible cookware must be used on induction
- Please note that induction compared a cooktops
  Make sure that the area below the induction cooktop is sufficiently ventilated opening cross-section > 50 cm<sup>2</sup>