
PC3B



BORA HiLight glass ceramic cooktop with 2 cooking zones: 3-ring/roaster





Technical data	
Supply voltage	380 - 415 V 2N
Frequency	50/60 Hz
Maximum power consumption	5.1 kW
Maximum power rating	5.1 kW
Minimum fuse protection	2 x 16 A
Power control	1 - 9, freely adjustable
	(Switching of 2/3 rings/roaster)
Weight (incl. accessories/packaging)	9.1 kg
Surface material	SCHOTT CERAN®
Power supply cable	1.5 m
Dimensions (width x depth x height)	370 x 540 x 50 mm
3-ring front cooking zone	800/1600/2500 W Ø
120/180/235 mm	
Roaster rear cooking zone	1500 W
Ø 165 mm	2600 W
290 x 165 mm	

Product description

- HiLight glass ceramic cooktop with 3-ring/roaster switching
- Residual heat display
- Childproofing feature

Scope of delivery

- PC3B HiLight glass ceramic cooktop
- PCSK2 control box with electronic controls (power level sleeve, control knob, adjustment plates)
- Mounting rails and straps
- Glass ceramic scraper
- Drilling template
- Height adjustment plate set
- Operating and installation instructions
- L1 L2 N 🖶 ■ Power supply cable

Accessories

(can be ordered separately)

■ PCKV10 100 cm cable extension